



Split plummer block housings

Designation	Shaft diameter	Appropriate bearing (basic designation)	Principal housing dimensions			
			A	H	H1	L
	da		mm			
SONL 217-517	74.612	2217 K	163	230	125	330
SONL 217-517	74.612	C 2217 K	163	230	125	330
SONL 217-517	74.612	22217 K	163	230	125	330
SONL 217-517	75	C 2217 K	163	230	125	330
SONL 217-517	75	22217 K	163	230	125	330
SONL 217-517	75	2217 K	163	230	125	330
SONL 218-518	80	C 2218 K	170	245	135	360
SONL 218-518	80	22218 K	170	245	135	360
SONL 218-518	80	2218 K	170	245	135	360
SONL 218-518	80.963	2218 K	170	245	135	360
SONL 218-518	80.963	C 2218 K	170	245	135	360
SONL 218-518	80.963	22218 K	170	245	135	360
SONL 220-520	87.313	C 2220 K	186	270	145	400
SONL 220-520	87.313	22220 K	186	270	145	400
SONL 220-520	87.313	2220 K	186	270	145	400
SONL 220-520	90	2220 K	186	270	145	400
SONL 220-520	90	C 2220 K	186	270	145	400
SONL 220-520	90	22220 K	186	270	145	400
SONL 222-522	100	2222 K	213	290	160	420
SONL 222-522	100	22222 K	213	290	160	420
SONL 222-522	100	C 2222 K	213	290	160	420
SONL 222-522	100.013	C 2222 K	213	290	160	420
SONL 222-522	100.013	22222 K	213	290	160	420
SONL 222-522	100.013	2222 K	213	290	160	420

SONL 224-524	106.362	22224 K	245	315	170	420
SONL 224-524	106.362	C 2224 K	245	315	170	420
SONL 224-524	110	22224 K	245	315	170	420
SONL 224-524	110	C 2224 K	245	315	170	420
SONL 226-526	112.713	22226 K	255	335	180	450
SONL 226-526	112.713	C 2226 K	255	335	180	450
SONL 226-526	115	22226 K	255	335	180	450
SONL 226-526	115	C 2226 K	255	335	180	450
SONL 228-528	125	22228 K	260	355	190	500
SONL 228-528	125	C 2228 K	260	355	190	500
SONL 228-528	125.412	22228 K	260	355	190	500
SONL 228-528	125.412	C 2228 K	260	355	190	500
SONL 230-530	131.762	22230 K	260	375	200	540
SONL 230-530	131.762	C 2230 K	260	375	200	540
SONL 230-530	135	22230 K	260	375	200	540
SONL 230-530	135	C 2230 K	260	375	200	540
SONL 232-532	138.113	22232 K	278	406	215	560
SONL 232-532	140	22232 K	278	406	215	560
SONL 234-534	150	C 2234 K	310	440	235	610
SONL 234-534	150	22234 CCK/W33	310	440	235	610
SONL 234-534	150.813	22234 CCK/W33	310	440	235	610
SONL 234-534	150.813	C 2234 K	310	440	235	610
SONL 236-536	160	22236 CCK/W33	320	455	245	650
SONL 236-536	163.513	22236 CCK/W33	320	455	245	650
SONL 238-538	170	C 2238 K	330	480	260	720
SONL 238-538	170	22238 CCK/W33	330	480	260	720
SONL 238-538	176.213	C 2238 K	330	480	260	720
SONL 238-538	176.213	22238 CCK/W33	330	480	260	720
SONL 240-540	180	22240 CCK/W33	338	510	275	730
SONL 240-540	182.563	22240 CCK/W33	338	510	275	730
SONL 244-544	200	C 2244 K	358	565	305	820
SONL 244-544	200	22244 CCK/W33	358	565	305	820
SONL 244-544	201.613	C 2244 K	358	565	305	820
SONL 244-544	201.613	22244 CCK/W33	358	565	305	820
SONL 248-548	220	22248 CCK/W33	368	625	340	900
SONL 248-548	227.013	22248 CCK/W33	368	625	340	900